

QUIET FAN DRYER 12 ton approximate holding capacity 6 ton per hour throughput*

The 600QF dryer is the solution for larger acreage farmers or for existing customers looking for an automated system. Automation gives huge labour savings and frees up time for staff to be involved in other operations at a very busy time of the year, it also allows drying around the clock increasing the throughput a day which keeps combines rolling even in the most difficult of years.

A powerful micro-processor Grain Guard control unit runs the dryer in automatic mode, constantly checking the operation of all moving components, the electrical supply and the state of the dryer throughout the loading, drying and unloading cycle. It determines the temperature at which the cool grain is unloaded from the dryer at the end of the drying cycle, checks that there is sufficient grain in the dryer and initiates the heating cycle automatically.

Supplied as standard with 38" custom built, in line centrifugal fan (74 dba). Unique self diagnostic electronic Grain Guard control. Centralised greaser location. Four electric motors. 60 ton an hour 12" diameter central auger 8" diameter loading auger with full length, 9ft 10" (3m) loading hopper (50 ton an hour loading capacity). LPG Gas fired burner. Epoxy powder coated outside sheets. Adjustable jacks, 4 tyres, grain sampler. Grain pressure splitter pelmet. Outlets for auxiliary loading and unloading motors. Horizontal discharge auger. 3-phase electric drive.

Electric drive models require 3-phase, 63 amp supply, earth and neutral on a dedicated circuit via residual current device and should be fitted by a qualified electrician.



SPECIFICATIONS FOR AUTO 600QF DRYER

| | |
|--|---|
| Drying capacity (21-16%)* | 6 t/hr |
| Holding capacity | 12t (17.5m³) |
| Height - working position, horizontal head / Sky-Vac | 15'3" (4.7m) / + 23" (580mm) |
| Height - transport with head removed | 13'6" (4.1m) |
| Width | 11' (3.4m) |
| Length - working position | 29' (8.9m) |
| Length - transport position | 20'5" (6.2m) |
| Weight - empty | 5940 lbs (2700kg) |
| Grain wall thickness | 18" (457mm) |
| Vertical auger size | 12" (305mm) |
| Loading auger size / unloading auger size | 8" (203mm) |
| Burner size - LP gas | 3,000,000 BTU/hr (879kW) |
| Fan type and size | In-line Centrifugal ø 38" (965mm) |
| Fan rating & outlet-static pressure | 16,000 ft³/min @ 1.5" (27,180m³/hr @ 3.74Mbar) |
| Recirculating time | 60 t/hr, 12-15min |
| Loading rate | 50 t/hr, 14min |
| Unloading rate | 50 t/hr, 14min |
| Electric power used | 4 motors (11,11,4, 1.5kw), 46.5amp |

* Throughput per hour assumed 5% moisture reduction from 21% to 16%. Includes loading, heating, cooling and unloading time.

OPICO's policy is one of continuous improvement and the right to change prices, specifications or equipment at any time without prior notice is reserved.