



HIGH CAPACITY, FASTER LOADING, GREATER THROUGHPUT, FASTER DRYING... 20 ton per hour throughput*

The 4810 is the 3810's larger sibling, it uses the same base but with an even larger holding capacity and plenum extension. Like the 3810 this means that the 4810 is effectively a fixed dryer but allows a significant increase in the size of the drying zone which means the drying capacity increases in proportion with its holding capacity unlike large winch up machines.

The fan, burner and auger capacities have all been increased in line with the holding capacity to achieve the highest throughput possible whilst still retaining all the other features common to the Magna range. When set up in conjunction with a wet holding facility the automated versions are amongst the most efficient and highest throughput batch dryers on the market.



- Stainless steel perforated screens, 1.5mm on the outside and 2.5mm on the inner plenum providing maximum airflow without compromise (particularly important when drying rape).
- Duax heat core – clean, efficient drying
- Low level burner – easy access for servicing and setting
- Bolt on plenum top – large drying zone
- 45cm, 160tph main auger – fast recirculation and unloading for quicker drying
- Fixed stainless steel screens – longevity.
- All susceptible components are supplied in stainless or galvanised finish.

DRYER SPECIFICATIONS

| Model | 4810 ELECTRIC / AUTO** |
|---------------------------------------|---|
| Drying capacity (21-16%)* | 20 t/hr |
| Holding capacity | 48t - 63m³ |
| Height - working position / Sky-Vac | 9.7m (31'10") / 9.92m (32'6") |
| Height - transport position | 4.4m (14'5") |
| Width | 4m (13'2") |
| Length - working position | 10.7m (35'5") |
| Length - transport position | 8m (13'2") |
| Weight - empty | 8600 Kgs |
| Grain wall thickness | 600mm (23½") |
| Vertical auger size | 450mm (17¾") |
| Loading auger size | 300mm (11¾") |
| Unloading auger size (Optional) | 300mm (11¾") |
| Burner size - Diesel / Kerosene | 5,550,000 BTU/hr (1,400,000 Kcal) |
| Fan type and size - quiet fan | Centrifugal ø 1120mm (44") |
| Fan rating and outlet static pressure | 100,000 m³/hr @ 10Mbar 58,860 CFM @ 4" |
| Recirculating time | 145 t/hr (20 min) |
| Loading rate | 120 t/hr (30 min) |
| Unloading rate | 120 t/hr (22 min) |
| Electric drive power used | 105kW (180Amp) - 6 Motors |
| Fuel tank capacity | 1000 litres |

* Throughput per hour assumed 5% moisture reduction from 21% to 16%. Includes loading, heating, cooling and unloading time.

** Electric drive requires 3-phase, 180amp supply, earth and neutral on a dedicated circuit via a residual current device
OPICO's policy is one of continuous improvement and the right to change prices, specifications or equipment at any time without prior notice is reserved.


KEY FEATURES



A highly efficient modulating diesel burner is easily accessible for servicing, simply remove the securing nut and slide the burner out for ease of maintenance.



In the servicing position the high and low flame jets are easily accessible. The air mixture can be altered when in working position.



Controls are protected with a weather and dust proof case with touch screen for easy monitoring.



All Magna dryers are fitted with a **DUAX Heat Core** burner. This uses heat retaining bricks similar to those in a storage heater, to heat the air as well as the burner. Inside the burner chamber is a steel barrel which is lined with the heat bricks. As the heat bricks

build up temperature, the whole burner core heats air as it is drawn past into the fan.